

AutoLight® Series

The AutoLight series provides a reliable and efficient solution for measuring light transmissibility through glass. Designed for accuracy and ease of use, these meters offer hands-free operation with built-in magnets for precise alignment. With advanced features like Bluetooth connectivity, users can easily capture, analyse, and store results, ensuring seamless compliance with inspection requirements.

Non-compliant window tint can significantly reduce a driver's field of vision, compromising the safety of both the driver and passengers. This reduced visibility makes it harder to see approaching vehicles, further increasing the risk of accidents.



AutoLight®

Standard Light Transmissibility Meter

This is the standard light transmissibility meter, designed for precise and reliable measurement of glass transmissibility. It provides accurate readings, ensuring compliance with inspection standards and regulations.

AutoLight® Plus

Standard Light Transmissibility Meter with Bluetooth

This is the standard light transmissibility meter with bluetooth connection allowing user connect to download data or connect to WorkShop Pro, the results can be collected and analysed and printed at the users convenience into a user-friendly report.

AutoLight® Magnetic

Hands-Free Light Transmissibility Meter

This hands-free light transmissibility meter enables users to measure glass transmissibility without holding the device. Built-in magnets ensure fast and precise alignment. In some regions, inspectors must photograph each test, making this meter a convenient and compliant solution.

AutoLight® Plus Magnetic

Hands-Free Light Transmissibility Meter with Bluetooth

This hands-free light transmissibility meter features built-in magnets for effortless alignment and a bluetooth connection allowing user connect to download data or connect to WorkShop Pro, the results can be collected and analysed and printed at the users convenience into a user-friendly report.

	Without Magnetic	With Magnetic (Hands-Free)
No Bluetooth	AutoLight®	AutoLight® Magnetic
With Bluetooth	AutoLight® Plus	AutoLight® Plus Magnetic

Note: Outer appearance and specifications are subject to change without prior notice



AutoTest Products Pty Ltd
69 Parsons Street
Kensington, VIC 3031
Australia

(+61) 3 8840 3000

sales@autotest.net.au



Specifications

Sensor Specification

- Spectral sensitivity conforming to photopic curve V (λ) of relative illuminous efficiency of the CIE 1931 standard observer for photopic vision
- Compliant with ISO 3538:1997

Light Source

- 2856°K \pm 50°K, conforming to CIE illuminate A
- Lamp voltage stabilised within \pm 0.1%
- Display: LED readout 0 – 100%, linear from 20 – 100%, \pm 3%

Accuracy

- Linear from 20 - 100%, \pm 3%

Display

- LED readout 0 - 100%
- Resolution: 0.1%
- Display is optimised for Digital photography

Power Source

- 2 x Energiser batteries (9 volt)

Product Feature

- Easy to operate by aligning two reader tubes
- Simple one button operation
- Can be used for side and rear windows, or windscreens
- Calculates the percentage of light transmitted through windows
- Lightweight (450g)
- Compact (190mm x 60mm)
- Automatic start function
- Comes with self-checking calibrated Glass
- Should be calibrated annually

Plus Feature

- Bluetooth Connect to software, Workshop Pro 10 and the printer

Magnetic Feature

- Magnetic for hands free operation

Want to see AutoLight in action?

Scan the QR code to watch the Demo Video



Upgrade to Magnetic for Hands-Free Operation

A single operator can conduct the test accurately and take a photo of the result, as required by some regulators.

