

AutoStop® Mini Plus2







The Mini Plus2 is a lightweight, versatile brake tester that uses advanced multi-channel sensors to measure tri-axial deceleration in vehicles and motorcycles. Compact, accurate, and built to meet the demands of modern workshops, it's the ultimate tool for professionals who value precision.

Suitable for:











Light Vehicles

Motorbikes

Trucks

Hand Brake

Product Feature

- Test all classes of Vehicles, both emergency & service brake & ABS
- Calculates and displays MFDD in accordance with the ECE R 13
- Simple & flexible installation
- Lightweight (< 500grms) and compact (90 x 200 x 35mm)
- Sunlight-readable full alphanumeric LCD display
- Automatic start function and shut-off after 15 minutes to preserve battery life
- Built-in integrity check and real time clock
- Calibration interval 12-months
- **ILAC Internationally Recognised** Calibration
- 12 months warranty
- Internet support hotline for diagnostics
- Comprehensive after-sales service and assistance
- USB-C and Bluetooth interface

Unique Feature

- Evaluates the performance of the brakes by measuring forward, deceleration, speed, distance to stop and lane deviation
- 200 Test Storage & operates for 8 hours in one charge
- Accurate and easy to use via a simple 12-button phone keypad
- Customer and vehicle detail entry via keypad
- Self Levelling & Self Aligning
- Optional PC Software connect via USB or Bluetooth.
- Connects with Bluetooth Printer
- 5V USB-C fast charging.



Check Out AutoStop Mini Plus in Action!

Scan the QR code to watch the

Note: Outer appearance and specifications are subject to change without prior notice















sales@autotest.net.au

AutoTest Products Pty Ltd

(+61) 3 8840 3000

AutoStop Mini Plus2

Date: July 2025



Optional Features

Input

Accelerometer: Accuracy ±2% Resolution 0.01g

Output

16 Character Full Alphanumeric LCD Display

Power Source

Lithium Polymer Battery Temperature Range-5°C - 50°C

Humidity

25% - 85%, Non-condensing

Specifications

- Optional GPS Version
- Bluetooth printer
- · Rare Earth magnet motorbike kit
- PC Software capability and graph
- · Rubber suction cup motorbike kit



HOW TO SET UP AUTOSTOP MINI PLUS IN 3 EASY STEPS



Attach Mini Plus to the dashboard, centre console or passenger seat so that the buttons and screen are clearly visible.



Turn on Mini Plus, accelerate the vehicle to the desired test speed (35km/hr) and apply the brakes until the vehicle is stationary.



After the vehicle has come to a stop Mini Plus evaluates, and displays forward, sideways, and vertical deceleration, distance to stop and lateral deviation within the lane



AutoTest Product Pty Ltd

www.autotest.net.au

69 Parsons Street, Kensington, VIC 3031, Australia

Phone: +(61) 3 8840 3000 E-mail: sales@autotest.net.au



DISTRIBUTOR